

Report No.:AX-DL-DE-15W-055

Test Time: 2025-09-28 16:14

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 50D

Luminous Width (mm): -45

Current: 0.113 A

Power Factor: 0.541

Luminous Length (mm): -45

Voltage: 221.9 V

Power: 13.70 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1269 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H45.9

Vertical Diffuse Angle(50%): V45.9

Luminaire Efficacy Rating (LER): 92.68

Max. Intensity: 2202.88 cd

S/MH(C0/C180): 0.74

Total Rated Lamp Lumens: 1269.0 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 2190.99 cd


Pos of Max. Intensity: H0 V2

S/MH(C90/C270): 0.74



Picture Of Luminaire



Luminous Intensity Distribution Curve




Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 2203 cd

(10%): 220 cd	(16%): 352 cd
(25%): 551 cd	(40%): 881 cd
(63%): 1388 cd	(100%): 2203 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 22.0 lx

(1%): 0.2 lx	(2%): 0.4 lx
(5%): 1.1 lx	(10%): 2.2 lx
(20%): 4.4 lx	(50%): 11.0 lx
(100%): 22.0 lx	

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 2191.0 lx
 (1%): 21.9 lx (2%): 43.8 lx
 (5%): 109.5 lx (10%): 219.1 lx
 (20%): 438.2 lx (50%): 1095.5 lx
 (100%): 2191.0 lx


C Plane (°): 0.0-180.0: 180.0
 Test Lab:
 Test Type: TYPE C
 Temperature:
 Operator:

Gamma Plane (°): 0.0-90.0: 1.0
 Test Device: CHL-6E
 Distance: 2.905 m
 Humidity:
 Inspector:

Unit: lm

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



C Plane (°): 0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°): 0.0-90.0: 1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	20.9	21.7	21.1	21.9	22.1	20.1	20.9	20.3	21.1	21.3
3H	20.7	21.4	21.0	21.7	21.9	19.9	20.6	20.2	20.9	21.1
4H	20.7	21.3	21.0	21.6	21.8	19.9	20.5	20.2	20.8	21.1
6H	20.6	21.2	20.9	21.5	21.8	19.8	20.4	20.1	20.7	21.0
8H	20.6	21.1	20.9	21.4	21.7	19.8	20.3	20.1	20.6	20.9
12H	20.5	21.1	20.9	21.4	21.7	19.7	20.3	20.1	20.6	20.9
X=4H Y=2H	20.7	21.3	21.0	21.6	21.9	19.9	20.5	20.2	20.8	21.1
3H	20.5	21.1	20.9	21.4	21.7	19.7	20.3	20.1	20.6	20.9
4H	20.4	20.9	20.8	21.3	21.6	19.6	20.1	20.0	20.5	20.8
6H	20.4	20.8	20.8	21.2	21.5	19.6	20.0	20.0	20.4	20.8
8H	20.3	20.7	20.7	21.1	21.5	19.5	19.9	19.9	20.3	20.7
12H	20.3	20.6	20.7	21.0	21.5	19.5	19.8	19.9	20.2	20.7
X=8H Y=4H	20.3	20.7	20.7	21.1	21.5	19.5	19.9	19.9	20.3	20.7
6H	20.2	20.5	20.7	21.0	21.4	19.4	19.7	19.9	20.2	20.6
8H	20.2	20.5	20.6	20.9	21.4	19.4	19.7	19.9	20.1	20.6
12H	20.1	20.4	20.6	20.8	21.3	19.3	19.6	19.8	20.0	20.5
X=12H Y=4H	20.3	20.6	20.7	21.0	21.5	19.5	19.8	19.9	20.2	20.7
6H	20.2	20.5	20.6	20.9	21.4	19.4	19.7	19.9	20.1	20.6
8H	20.1	20.4	20.6	20.8	21.3	19.3	19.6	19.8	20.0	20.5
Variations with the observer position at spacings:										
S=1.0H	+5.4/-11.4					+5.2/-11.8				
S=1.5H	+8.2/-23.3					+8.0/-25.2				
S=2.0H	+10.2/-1.\$					+10.0/-1.\$				

Calculate in accordance with CIE Pub.117. The table is revised with 1269lm ($8\log(F/F_0) = 0.8$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	666	52.5
FL (0°-30°)	554	43.6
FM (30°-60°)	112	8.8
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	603	47.5
BL (0°-30°)	512	40.3
BM (30°-60°)	91	7.2
BH (60°-80°)	0	0.0
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B2 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	2191.3	2.1	2.1	0.17	0.17
1.0-2.0	2185.5	6.3	8.4	0.49	0.66
2.0-3.0	2167.0	10.4	18.7	0.82	1.48
3.0-4.0	2136.2	14.3	33.0	1.13	2.60
4.0-5.0	2099.0	18.1	51.1	1.42	4.03
5.0-6.0	2061.5	21.7	72.8	1.71	5.73
6.0-7.0	2024.7	25.1	97.9	1.98	7.71
7.0-8.0	1988.9	28.5	126.4	2.24	9.96
8.0-9.0	1953.7	31.7	158.0	2.50	12.45
9.0-10.0	1918.0	34.7	192.8	2.74	15.19
10.0-11.0	1880.9	37.6	230.3	2.96	18.15
11.0-12.0	1842.4	40.3	270.6	3.17	21.32
12.0-13.0	1802.0	42.8	313.4	3.37	24.70
13.0-14.0	1758.4	45.0	358.4	3.55	28.24
14.0-15.0	1709.7	46.9	405.3	3.70	31.94
15.0-16.0	1654.7	48.5	453.8	3.82	35.76
16.0-17.0	1595.5	49.7	503.5	3.92	39.68
17.0-18.0	1532.1	50.5	554.1	3.98	43.66
18.0-19.0	1463.6	50.9	605.0	4.01	47.67
19.0-20.0	1390.8	50.9	655.9	4.01	51.68
20.0-21.0	1313.0	50.4	706.3	3.97	55.66
21.0-22.0	1229.0	49.4	755.7	3.89	59.55
22.0-23.0	1139.5	47.8	803.5	3.77	63.32
23.0-24.0	1047.0	45.8	849.3	3.61	66.93
24.0-25.0	952.9	43.3	892.6	3.41	70.34
25.0-26.0	859.4	40.6	933.2	3.20	73.54
26.0-27.0	768.7	37.6	970.8	2.96	76.50
27.0-28.0	682.5	34.6	1005.4	2.72	79.22
28.0-29.0	602.1	31.5	1036.9	2.48	81.71
29.0-30.0	527.4	28.5	1065.4	2.24	83.95
30.0-31.0	460.2	25.6	1091.0	2.02	85.97
31.0-32.0	400.5	22.9	1113.9	1.81	87.78
32.0-33.0	346.2	20.4	1134.3	1.61	89.39
33.0-34.0	297.9	18.0	1152.4	1.42	90.81
34.0-35.0	255.5	15.9	1168.2	1.25	92.06
35.0-36.0	218.0	13.9	1182.1	1.09	93.15

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:


Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	185.6	12.1	1194.2	0.95	94.10
37.0-38.0	157.9	10.5	1204.8	0.83	94.93
38.0-39.0	134.0	9.2	1213.9	0.72	95.66
39.0-40.0	113.8	7.9	1221.8	0.63	96.28
40.0-41.0	96.8	6.9	1228.7	0.54	96.83
41.0-42.0	82.5	6.0	1234.7	0.47	97.30
42.0-43.0	69.9	5.2	1239.9	0.41	97.71
43.0-44.0	58.5	4.4	1244.3	0.35	98.05
44.0-45.0	48.5	3.7	1248.1	0.29	98.35
45.0-46.0	40.1	3.1	1251.2	0.25	98.59
46.0-47.0	33.5	2.7	1253.8	0.21	98.80
47.0-48.0	28.7	2.3	1256.2	0.18	98.99
48.0-49.0	24.9	2.0	1258.2	0.16	99.15
49.0-50.0	21.5	1.8	1260.0	0.14	99.29
50.0-51.0	18.6	1.6	1261.6	0.12	99.41
51.0-52.0	15.9	1.4	1262.9	0.11	99.52
52.0-53.0	13.5	1.2	1264.1	0.09	99.61
53.0-54.0	11.3	1.0	1265.1	0.08	99.69
54.0-55.0	9.4	0.8	1266.0	0.07	99.76
55.0-56.0	7.9	0.7	1266.7	0.06	99.81
56.0-57.0	6.6	0.6	1267.3	0.05	99.86
57.0-58.0	5.3	0.5	1267.8	0.04	99.90
58.0-59.0	4.2	0.4	1268.2	0.03	99.93
59.0-60.0	3.3	0.3	1268.5	0.02	99.96
60.0-61.0	2.4	0.2	1268.7	0.02	99.97
61.0-62.0	1.6	0.2	1268.9	0.01	99.99
62.0-63.0	1.0	0.1	1268.9	0.01	99.99
63.0-64.0	0.5	0.1	1269.0	0.00	100.00
64.0-65.0	0.2	0.0	1269.0	0.00	100.00
65.0-66.0	0.1	0.0	1269.0	0.00	100.00
66.0-67.0	0.0	0.0	1269.0	0.00	100.00
67.0-68.0	0.0	0.0	1269.0	0.00	100.00
68.0-69.0	0.0	0.0	1269.0	0.00	100.00
69.0-70.0	0.0	0.0	1269.0	0.00	100.00
70.0-71.0	0.0	0.0	1269.0	0.00	100.00
71.0-72.0	0.0	0.0	1269.0	0.00	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:



Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	2191.0	2191.0								
G1.0	2197.9	2185.3								
G2.0	2202.9	2156.0								
G3.0	2192.4	2116.9								
G4.0	2159.5	2076.0								
G5.0	2123.4	2037.0								
G6.0	2088.1	1997.6								
G7.0	2054.1	1959.1								
G8.0	2019.5	1923.1								
G9.0	1987.7	1884.4								
G10.0	1954.7	1845.3								
G11.0	1919.8	1803.8								
G12.0	1883.8	1762.2								
G13.0	1847.3	1714.7								
G14.0	1810.8	1660.8								
G15.0	1765.6	1601.8								
G16.0	1713.3	1538.1								
G17.0	1657.9	1472.6								
G18.0	1597.6	1400.3								
G19.0	1534.0	1322.5								
G20.0	1466.4	1240.2								
G21.0	1393.7	1151.5								
G22.0	1312.1	1058.7								
G23.0	1223.1	964.4								
G24.0	1130.4	870.0								
G25.0	1035.6	775.5								
G26.0	939.8	686.7								
G27.0	843.4	605.1								
G28.0	752.1	529.5								
G29.0	665.7	461.1								
G30.0	583.2	399.8								
G31.0	513.2	344.6								
G32.0	447.4	296.6								
G33.0	386.3	254.4								
G34.0	333.8	217.0								
G35.0	286.0	185.0								
G36.0	243.3	157.8								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	207.1	134.3								
G38.0	175.8	114.3								
G39.0	148.2	97.9								
G40.0	126.0	83.2								
G41.0	107.0	71.2								
G42.0	91.5	60.3								
G43.0	77.9	49.9								
G44.0	65.9	40.1								
G45.0	54.4	33.6								
G46.0	43.3	29.1								
G47.0	35.9	25.5								
G48.0	31.3	22.0								
G49.0	27.1	19.0								
G50.0	23.8	16.2								
G51.0	20.7	13.7								
G52.0	17.8	11.5								
G53.0	15.1	9.6								
G54.0	12.7	7.8								
G55.0	10.8	6.4								
G56.0	9.2	5.3								
G57.0	7.7	4.2								
G58.0	6.2	3.4								
G59.0	4.8	2.5								
G60.0	3.9	1.8								
G61.0	2.9	0.8								
G62.0	2.1	0.4								
G63.0	1.4	0.0								
G64.0	0.7	0.0								
G65.0	0.1	0.0								
G66.0	0.1	0.0								
G67.0	0.0	0.0								
G68.0	0.0	0.0								
G69.0	0.0	0.0								
G70.0	0.0	0.0								
G71.0	0.0	0.0								
G72.0	0.0	0.0								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:


Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:



Unit: cd

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector: