

Report No.: AX-TL-AX-15W-062

Test Time: 2023-09-09 14:47

## Luminaire Property

Luminaire Category: Bridgelux V10A 3000K CRI90

Voltage: 219.1 V

Current: 0.120 A

Power: 14.10 W

Power Factor: 0.531

## Photometric Results

CIE Class: Direct

Measurement Flux: 1546.1 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H37.9

Vertical Diffuse Angle(50%): V37.9

Luminaire Efficacy Rating (LER): 110

Max. Intensity: 3449.34 cd

Total Rated Lamp Lumens: 1546.1 lm

Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 3449.33 cd

Pos of Max. Intensity: H0 V0

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G0

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


## Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## Isocandela (rectangle)



Imax (100%): 3449 cd

( 10%): 345 cd	( 16%): 552 cd
( 25%): 862 cd	( 40%): 1380 cd
( 63%): 2173 cd	(100%): 3449 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


## IsoLux Plot




C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## Illuminance at a Distance



## Vertical IsoLux Plot




Lowest(m): 1m    Highest(m): 11    Max Lux: 3449

( 1%): 34 lx	( 2%): 69 lx
( 5%): 172 lx	( 10%): 345 lx
( 20%): 690 lx	( 50%): 1725 lx
(100%): 3449 lx	

C Plane (°):0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

## The average illuminance effective figure



C Plane (°): 0.0-180.0: 180.0  
Test Lab:  
Test Type: TYPE C  
Temperature:  
Operator:

Gamma Plane (°): 0.0-90.0: 5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector:



## Unit: cd

Gamma Plane (°):0.0-90.0:5.0  
Test Device: CHL-6E  
Distance: 3.000 m  
Humidity:  
Inspector: