

Report No.:AX-TL-SP-12W-045

Test Time: 2023-07-13 14:44

Luminaire Property

Luminaire Category: Bridgelux V4HD 3000K CRI90

Voltage: 209.3 V

Current: 0.143 A

Power: 11.80 W

Power Factor: 0.382

Photometric Results

CIE Class: Direct

Measurement Flux: 700.8 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H29.6

Vertical Diffuse Angle(50%): V29.6

Luminaire Efficacy Rating (LER): 59

Max. Intensity: 2163.71 cd

Total Rated Lamp Lumens: 700.8 lm


Efficiency: 100%

Upward Ratio: 0%


Central Intensity: 2155.34 cd

Pos of Max. Intensity: H180 V5

Picture Of Luminaire



Luminous Intensity Distribution Curve



— C0-C180 — C90-C270 — G5

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0



Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:


Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 2164 cd

(10%): 216 cd	(16%): 346 cd
(25%): 541 cd	(40%): 865 cd
(63%): 1363 cd	(100%): 2164 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10m Max Lux(100%): 22 lx			
— (1%):	0 lx	— (2%):	0 lx
— (5%):	1 lx	— (10%):	2 lx
— (20%):	4 lx	— (50%):	11 lx
— (100%):	22 lx		

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1m Highest(m): 11 Max Lux: 2155

(1%): 22 lx	(2%): 43 lx
(5%): 108 lx	(10%): 216 lx
(20%): 431 lx	(50%): 1078 lx
(100%): 2155 lx	

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:5.0


Test Device: CHL-6E

Distance: 3.000 m

Humidity:

Inspector:

The average illuminance effective figure



Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector:

Unit: cd

Gamma Plane (°):0.0-90.0:5.0
Test Device: CHL-6E
Distance: 3.000 m
Humidity:
Inspector: