

Report No.:AX-MG-FL-AC-F-20W-220

Test Time: 2025-09-20 16:59

Luminaire Property

Luminaire Manufacturer:

Luminaire Description: 15D

Luminous Width (mm): -20

Current: 0.091 A

Power Factor: 0.942

Luminous Length (mm): -430

Voltage: 233.5 V

Power: 20.10 W

Photometric Results

CIE Class: Direct

Measurement Flux: 1612.7 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(50%): H21.6

Vertical Diffuse Angle(50%): V21.6

Luminaire Efficacy Rating (LER): 80.28

Max. Intensity: 8854.13 cd

S/MH(C0/C180): 0.37

Total Rated Lamp Lumens: 1612.7 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 8854.13 cd


Pos of Max. Intensity: H0 V0

S/MH(C90/C270): 0.37



Picture Of Luminaire



Luminous Intensity Distribution Curve




Luminous Intensity Distribution Curve



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:


Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Isocandela (rectangle)



Imax (100%): 8854 cd

(10%): 885 cd	(16%): 1417 cd
(25%): 2214 cd	(40%): 3542 cd
(63%): 5578 cd	(100%): 8854 cd

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:

IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 88.5 lx

(1%): 0.9 lx	(2%): 1.8 lx
(5%): 4.4 lx	(10%): 8.9 lx
(20%): 17.7 lx	(50%): 44.3 lx
(100%): 88.5 lx	

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0


Test Device: CHL-6E

Distance: 2.905 m


Humidity:

Inspector:

Illuminance at a Distance



Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 11.0m Max Lux: 8854.1 lx

(1%): 88.5 lx	(2%): 177.1 lx
(5%): 442.7 lx	(10%): 885.4 lx
(20%): 1770.8 lx	(50%): 4427.1 lx
(100%): 8854.1 lx	

C Plane (°): 0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°): 0.0-90.0: 1.0

Test Device: CHL-6E

Distance: 2.905 m


Humidity:

Inspector:

Unit: lm

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

The Average Illuminance Effective Figure



UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	8.2	8.8	8.4	9.0	9.2	6.8	7.4	7.0	7.6	7.8
3H	8.1	8.6	8.3	8.8	9.0	6.7	7.2	7.0	7.5	7.7
4H	8.0	8.5	8.3	8.7	9.0	6.6	7.1	6.9	7.4	7.6
6H	7.9	8.4	8.2	8.7	8.9	6.6	7.0	6.9	7.3	7.6
8H	7.9	8.3	8.2	8.6	8.9	6.5	7.0	6.9	7.3	7.6
12H	7.8	8.3	8.2	8.6	8.9	6.5	6.9	6.8	7.2	7.5
X=4H Y=2H	8.0	8.5	8.3	8.7	9.0	6.6	7.1	6.9	7.3	7.6
3H	7.8	8.3	8.2	8.6	8.9	6.5	6.9	6.8	7.2	7.5
4H	7.8	8.1	8.1	8.5	8.8	6.4	6.8	6.8	7.1	7.5
6H	7.7	8.0	8.1	8.4	8.8	6.3	6.7	6.7	7.0	7.4
8H	7.6	7.9	8.0	8.3	8.7	6.3	6.6	6.7	7.0	7.4
12H	7.6	7.8	8.0	8.3	8.7	6.2	6.5	6.7	6.9	7.3
X=8H Y=4H	7.6	7.9	8.0	8.3	8.7	6.3	6.6	6.7	7.0	7.4
6H	7.5	7.8	8.0	8.2	8.6	6.2	6.4	6.6	6.9	7.3
8H	7.5	7.7	7.9	8.1	8.6	6.1	6.3	6.6	6.8	7.3
12H	7.4	7.6	7.9	8.1	8.6	6.1	6.3	6.6	6.7	7.2
X=12H Y=4H	7.6	7.8	8.0	8.3	8.7	6.2	6.5	6.7	6.9	7.3
6H	7.5	7.7	7.9	8.1	8.6	6.1	6.3	6.6	6.8	7.3
8H	7.4	7.6	7.9	8.1	8.6	6.1	6.3	6.6	6.7	7.2
Variations with the observer position at spacings:										
S=1.0H	+6.0/-18.3					+5.6/-14.8				
S=1.5H	+8.8/-26.2					+8.4/-18.2				
S=2.0H	+10.8/-25.0					+10.4/-22.5				

Calculate in accordance with CIE Pub.117. The table is revised with 1613lm ($8\log(F/F_0) = 1.7$).

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	852	52.8
FL (0°-30°)	813	50.4
FM (30°-60°)	39	2.4
FH (60°-80°)	0	0.0
FVH (80°-90°)	0	0.0
BACK LIGHT	761	47.2
BL (0°-30°)	733	45.4
BM (30°-60°)	27	1.7
BH (60°-80°)	1	0.1
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight, Uplight, Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B2 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V, Area Light)	B2 U0 G0

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	8826.4	8.4	8.4	0.52	0.52
1.0-2.0	8715.8	25.0	33.5	1.55	2.08
2.0-3.0	8498.5	40.7	74.1	2.52	4.60
3.0-4.0	8185.3	54.8	128.9	3.40	7.99
4.0-5.0	7787.9	67.0	195.9	4.15	12.15
5.0-6.0	7323.4	77.0	272.9	4.77	16.92
6.0-7.0	6809.8	84.5	357.4	5.24	22.16
7.0-8.0	6262.1	89.6	447.1	5.56	27.72
8.0-9.0	5696.6	92.3	539.4	5.73	33.45
9.0-10.0	5128.2	92.8	632.2	5.76	39.20
10.0-11.0	4571.4	91.4	723.6	5.66	44.87
11.0-12.0	4040.2	88.3	811.9	5.48	50.34
12.0-13.0	3540.9	84.0	895.9	5.21	55.56
13.0-14.0	3077.9	78.8	974.7	4.89	60.44
14.0-15.0	2659.8	73.0	1047.8	4.53	64.97
15.0-16.0	2283.0	66.9	1114.7	4.15	69.12
16.0-17.0	1945.7	60.6	1175.3	3.76	72.88
17.0-18.0	1650.8	54.4	1229.7	3.38	76.25
18.0-19.0	1395.9	48.6	1278.3	3.01	79.26
19.0-20.0	1177.5	43.1	1321.4	2.67	81.94
20.0-21.0	991.1	38.1	1359.4	2.36	84.30
21.0-22.0	832.1	33.4	1392.9	2.07	86.37
22.0-23.0	697.6	29.3	1422.2	1.82	88.19
23.0-24.0	585.6	25.6	1447.8	1.59	89.77
24.0-25.0	492.2	22.4	1470.1	1.39	91.16
25.0-26.0	413.6	19.5	1489.7	1.21	92.37
26.0-27.0	347.6	17.0	1506.7	1.05	93.43
27.0-28.0	292.4	14.8	1521.5	0.92	94.35
28.0-29.0	246.1	12.9	1534.4	0.80	95.14
29.0-30.0	206.8	11.2	1545.5	0.69	95.84
30.0-31.0	173.8	9.7	1555.2	0.60	96.44
31.0-32.0	146.4	8.4	1563.6	0.52	96.96
32.0-33.0	123.2	7.3	1570.9	0.45	97.41
33.0-34.0	103.2	6.2	1577.1	0.39	97.79
34.0-35.0	86.7	5.4	1582.5	0.33	98.13
35.0-36.0	72.7	4.6	1587.1	0.29	98.41

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	59.7	3.9	1591.0	0.24	98.66
37.0-38.0	50.2	3.4	1594.4	0.21	98.86
38.0-39.0	42.1	2.9	1597.2	0.18	99.04
39.0-40.0	33.7	2.4	1599.6	0.15	99.19
40.0-41.0	27.7	2.0	1601.6	0.12	99.31
41.0-42.0	23.5	1.7	1603.3	0.11	99.42
42.0-43.0	19.3	1.4	1604.7	0.09	99.51
43.0-44.0	15.1	1.1	1605.8	0.07	99.58
44.0-45.0	11.6	0.9	1606.7	0.06	99.63
45.0-46.0	9.1	0.7	1607.4	0.04	99.68
46.0-47.0	7.4	0.6	1608.0	0.04	99.71
47.0-48.0	6.0	0.5	1608.5	0.03	99.74
48.0-49.0	4.9	0.4	1608.9	0.03	99.77
49.0-50.0	4.6	0.4	1609.3	0.02	99.79
50.0-51.0	5.3	0.4	1609.7	0.03	99.82
51.0-52.0	5.6	0.5	1610.2	0.03	99.85
52.0-53.0	4.9	0.4	1610.7	0.03	99.87
53.0-54.0	3.5	0.3	1611.0	0.02	99.89
54.0-55.0	2.1	0.2	1611.1	0.01	99.91
55.0-56.0	1.0	0.1	1611.2	0.01	99.91
56.0-57.0	0.3	0.0	1611.3	0.00	99.91
57.0-58.0	0.0	0.0	1611.3	0.00	99.91
58.0-59.0	0.3	0.0	1611.3	0.00	99.92
59.0-60.0	1.1	0.1	1611.4	0.01	99.92
60.0-61.0	1.4	0.1	1611.5	0.01	99.93
61.0-62.0	1.1	0.1	1611.6	0.01	99.94
62.0-63.0	0.7	0.1	1611.7	0.00	99.94
63.0-64.0	0.7	0.1	1611.8	0.00	99.94
64.0-65.0	0.7	0.1	1611.8	0.00	99.95
65.0-66.0	0.7	0.1	1611.9	0.00	99.95
66.0-67.0	0.7	0.1	1612.0	0.00	99.96
67.0-68.0	0.7	0.1	1612.1	0.00	99.96
68.0-69.0	1.1	0.1	1612.2	0.01	99.97
69.0-70.0	1.4	0.1	1612.3	0.01	99.98
70.0-71.0	1.4	0.1	1612.5	0.01	99.99
71.0-72.0	1.4	0.1	1612.6	0.01	100.00

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:

Candlepower Table

Unit: cd

G\C	C0.0	C180.0								
G0.0	8854.1	8854.1								
G1.0	8819.0	8778.3								
G2.0	8677.2	8588.7								
G3.0	8428.6	8299.4								
G4.0	8093.0	7920.3								
G5.0	7675.9	7462.5								
G6.0	7205.5	6949.9								
G7.0	6694.3	6389.6								
G8.0	6157.9	5806.8								
G9.0	5607.4	5214.2								
G10.0	5063.9	4627.2								
G11.0	4530.3	4064.1								
G12.0	4031.8	3534.6								
G13.0	3561.3	3036.1								
G14.0	3126.0	2588.1								
G15.0	2735.6	2189.3								
G16.0	2380.3	1827.0								
G17.0	2061.5	1513.8								
G18.0	1783.5	1244.2								
G19.0	1539.1	1016.7								
G20.0	1325.7	828.5								
G21.0	1136.1	674.1								
G22.0	976.0	542.1								
G23.0	832.8	439.5								
G24.0	713.4	356.7								
G25.0	608.1	290.7								
G26.0	518.2	237.3								
G27.0	439.5	195.2								
G28.0	372.1	162.9								
G29.0	314.6	134.8								
G30.0	265.4	112.3								
G31.0	223.3	94.1								
G32.0	188.2	80.1								
G33.0	157.3	67.4								
G34.0	130.6	57.6								
G35.0	110.9	47.8								
G36.0	89.9	42.1								

C Plane (°):0.0-180.0: 180.0

Test Lab:

Test Type: TYPE C

Temperature:

Operator:

Gamma Plane (°):0.0-90.0:1.0

Test Device: CHL-6E

Distance: 2.905 m

Humidity:

Inspector:


Candlepower Table (Continue 1)

Unit: cd

G\C	C0.0	C180.0								
G37.0	73.0	33.7								
G38.0	63.2	30.9								
G39.0	49.2	25.3								
G40.0	39.3	21.1								
G41.0	32.3	18.3								
G42.0	28.1	15.4								
G43.0	21.1	12.6								
G44.0	15.4	11.2								
G45.0	12.6	7.0								
G46.0	9.8	7.0								
G47.0	8.4	4.2								
G48.0	5.6	5.6								
G49.0	4.2	4.2								
G50.0	4.2	5.6								
G51.0	4.2	7.0								
G52.0	4.2	7.0								
G53.0	4.2	4.2								
G54.0	1.4	4.2								
G55.0	1.4	1.4								
G56.0	0.0	1.4								
G57.0	0.0	0.0								
G58.0	0.0	0.0								
G59.0	0.0	1.4								
G60.0	0.0	2.8								
G61.0	0.0	2.8								
G62.0	0.0	1.4								
G63.0	0.0	1.4								
G64.0	0.0	1.4								
G65.0	0.0	1.4								
G66.0	0.0	1.4								
G67.0	0.0	1.4								
G68.0	0.0	1.4								
G69.0	0.0	2.8								
G70.0	0.0	2.8								
G71.0	0.0	2.8								
G72.0	0.0	2.8								
G73.0	0.0	0.0								

C Plane (°):0.0-180.0: 180.0
Test Lab:
Test Type: TYPE C
Temperature:
Operator:

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector:



Unit: cd

Gamma Plane (°):0.0-90.0:1.0
Test Device: CHL-6E
Distance: 2.905 m
Humidity:
Inspector: